Material Safety Data Sheet

Material: 60005014

Version: 1.1 (US)

ELASTOSIL® LR 3003/40 A

Date of last alteration: 19/12/2012

1. Product and company identification 1.1 Identification of the substance or preparation: ELASTOSIL® LR 3003/40 A **Commercial product name:** Use of substance / preparation Industrial. Raw material for: elastomer products . 1.2 Company/undertaking identification: Manufacturer/distributor: Wacker Chemie AG Hanns-Seidel-Platz 4 81737 München Germany Customer information: Wacker Chemical Corporation 3301 Sutton Road Adrian, Michigan 49221-9397 USA InfoLine: Tel (517) 264-8240, Fax (517) 264-8740 Hours of operation: Monday - Friday, 8 am to 5 pm (eastern standard time) Corporate website: www.wacker.com Emergency telephone no. (24h): (517) 264-8500 (800) 424-9300 (CHEMTREC, USA) Transportation emergency: (703) 527-3887 (CHEMTREC, international)

Date of print: 05/28/2014

This MSDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2. Composition/information on ingredients

2.1 Chemical characterization (preparation)

Chemical characteristics

Polydimethylsiloxane with vinyl groups and auxiliary

2.2 Information on ingredients:

This material does not contain any hazardous substances at or above OSHA and WHMIS reportable levels. Due to the physical nature of this material (paste), exposure to dusts/particulates is not expected.

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in Section 2 are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product.

3. Hazards identification

3.1 Hazards classifications

HMIS® rating (product as packaged):

Health: 1 Fire: 1

Reactivity: 0

PPE: B

Hazardous Materials Identification System and HMIS are registered trademarks of the National Paint and Coatings Association. Note: Respiratory protection is only recommended in the event that ventilation or engineering controls are unable to maintain exposures below recommended levels; or in the event of a spill or other emergency response situation.

Canadian WHMIS Classification: None.

3.2 Emergency overview and potential hazards

This material is not hazardous under OSHA criteria. This material is not hazardous under WHMIS criteria.

Physical Hazards:

No known physical hazards.

Material Safety Data Sheet

Material: 60005014

ELASTOSIL® LR 3003/40 A

Version: 1.1 (US)

Date of print: 05/28/2014

Date of last alteration: 19/12/2012

Method:

Acute health effects Route of entry or possible contact: eyes , skin , ingestion Eye contact: May cause slight eye irritation. Skin contact: No acute toxic skin effects are expected. Inhalation: No acute toxic respiratory tract effects are expected. Inhalation is not expected due to low vapor pressure or high viscosity. Ingestion: Ingestion is not expected in industrial use. Additional information on acute health effects:

The health hazard evaluation is based on test results and/or on known properties of ingredients. Due to the physical nature of this material (paste), exposure to dusts/particulates is not expected.

3.3 Further information:

Chronic health effects:

No known or expected chronic health effects.

Medical conditions which may be aggravated by exposure:

none known

Target organs affected:

No known internal organ effects.

Signs and Symptoms of Exposure:

Refer to Acute Health Effects, listed above.

Carcinogens/Reproductive toxins:

There are no carcinogenic ingredients present at or over 0.1% in this material. This material does not contain any reproductive toxins at or above OSHA or WHMIS reportable levels.

See Section 11 for Toxicological Information, if any.

4. First-aid measures

4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

4.2 After inhalation

Material cannot be inhaled under normal conditions. No special measures required.

4.3 After contact with the skin

For skin contact: Wipe off excess material with cloth or paper. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

4.5 After swallowing

After swallowing No special treatment is required.

5. Fire-fighting measures

5.1 Flammable properties:

Property:	Value:
Flash point	> 150 °C (> 302 °F)
Boiling point / boiling range	no data available
Lower explosion limit (LEL)	not applicable
Upper explosion limit (UEL)	not applicable
Ignition temperature	> 210 °C (> 410 °F)

Material Safety Data Sheet

Material: 60005014

Version: 1.1 (US)

5.2

.

ELASTOSIL® LR 3003/40 A

Date of print: 05/28/2014

Date of last alteration: 19/12/2012

This material does not present any unusual fire or explosion hazards.

5.3 Recommended extinguishing media:

Fire and explosion hazards:

water-spray , dry chemical , alcohol-resistant foam , carbon dioxide , sand .

5.4 Unsuitable extinguishing media:

water jet

5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases Hazardous decomposition products: carbon dioxide, carbon monoxide, formaldehyde, silicon dioxide and incompletely burnt hydrocarbons.

5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water.

6. Accidental release measures

6.1 Precautions:

No special measures required.

HAZWOPER PPE Level: D

6.2 Containment:

Prevent material from entering sewers or surface waters.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

6.3 Methods for cleaning up

Scoop up large quantities after dusting surfaces with sand or Fuller's earth to prevent sticking. Sweep or scrape up the spilled material and place in an appropriate chemical waste container. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

7. Handling and storage

7.1 Handling

Precautions for safe handling:

No special protective measures required.

Precautions against fire and explosion:

No special precautions against fire and explosion required.

7.2 Storage

Conditions for storage rooms and vessels: none known

Advice for storage of incompatible materials:

not applicable

Further information for storage: Keep container tightly closed. Store in a dry and cool place.

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use with adequate ventilation.

Material Safety Data Sheet

Material: 60005014

ELASTOSIL® LR 3003/40 A

Date of last alteration: 19/12/2012

Version: 1.1 (US)

Date of print: 05/28/2014

Local exhaust: not necessary

8.2 Associate substances with specific control parameters such as limit values

none known

8.3 Personal protection equipment (PPE)

Respiratory protection:

Respiratory protection is not normally required.

Hand protection:

Recommendation: Any liquid-tight rubber or vinyl gloves.

Eye protection:

Recommendation: Safety glasses with side shields.

Other protective clothing or equipment:

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

8.4 General hygiene and protection measures:

When handling do not eat, drink, smoke or apply cosmetics. Wash thoroughly after handling.

9. Physical and chemical properties

9.1 Appearance

Physical state / form	paste
Colour	transparent
Odour	slight

9.2 Safety parameters

Property:	Value:	Method:
Melting point / melting range	no data available	
Boiling point / boiling range	no data available	
Flash point	> 150 °C (> 302 °F)	
Ignition temperature	> 210 °C (> 410 °F)	
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL)	not applicable	
Vapour pressure	not applicable	
Density	1.13 g/cm ³ at 23 °C (73 °F), at 1013 hPa	(ISO 1183-1 A)
Water solubility / miscibility	insoluble	· · · ·
pH-Value	not applicable	
Viscosity (dynamic)	950000 mPa.s at 25 °C (77 °F)	(DIN EN ISO 3219)

10. Stability and reactivity

10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

none known

10.3 Materials to avoid

none known

10.4 Hazardous decomposition products

If stored and handled properly: none known . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.

Material Safety Data Sheet

Material: 60005014

ELASTOSIL® LR 3003/40 A

Version: 1.1 (US)

Date of print: 05/28/2014

Date of last alteration: 19/12/2012

11. Toxicological information

11.1 Information on toxicological effects

Toxicological testing has not been conducted with this material.

11.1.1 Acute toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Acute toxicity estimate (ATE):

ATE_{mix} (oral): > 2000 mg/kg

11.1.2 Skin corrosion/irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.3 Serious eye damage / eye irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.4 Respiratory or skin sensitization

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

12. Ecological information

12.1 Toxicity

Assessment:

For the product as a whole, no test data is available. According to current knowledge adverse effects on water purification plants are not expected.

Material Safety Data Sheet

Material: 60005014

ELASTOSIL® LR 3003/40 A

Version: 1.1 (US)

Date of print: 05/28/2014

Date of last alteration: 19/12/2012

12.2 Persistence and degradability

Assessment:

Biologically not degradable. Insoluble in water. Separation by sedimentation.

12.3 Bioaccumulative potential

Assessment:

No adverse effects expected.

12.4 Mobility in soil

Assessment:

Assessment.

Insoluble in water. No adverse effects expected.

12.5 Other adverse effects

none known

13. Disposal considerations

13.1 Product disposal

Recommendation:

Material that cannot be used or chemically reprocessed should be disposed of at an approved facility in accordance with any applicable governmental regulations.

13.2 Packaging disposal

Recommendation:

Containers should be completely emptied before recycling as specified in government regulations. Empty containers should be sent to an approved recycling facility.

14. Transport information

14.1 US DOT & CANADA TDG SURFACE

Valuation Not regulated for transport

14.2 Transport by sea IMDG-Code

Valuation: Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation Not regulated for transport

15. Regulatory information

15.1 U.S. Federal regulations

TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

TSCA 12(b) Export Notification:

This material does not contain any TSCA 12(b) regulated chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

This product does not present any SARA 311/312 hazards.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

Material Safety Data Sheet

Material: 60005014

Version: 1.1 (US)

ELASTOSIL® LR 3003/40 A

Date of print: 05/28/2014

Date of last alteration: 19/12/2012

HAPS (Hazardous Air Pollutants):

This material does not contain any hazardous air pollutants.

15.2 U.S. State regulations

California Proposition 65 Carcinogens:

This material does not contain any chemicals known to the state of California to cause cancer.

California Proposition 65 Reproductive Toxins:

This material does not contain any chemicals known to the state of California to cause reproductive effects.

Massachusetts Substance List:

This material contains no listed components.

New Jersey Right-to-Know Hazardous Substance List:

This material contains no listed components.

Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

15.3 Canadian regulations

This product has been classified in accordance with the Hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Hazard Classes:

None.

DSL Status:

This material or its components are listed on the Canadian Domestic Substances List.

Canadian Ingredient Disclosure List:

This material contains no listed components.

15.4 Other international regulations

EU Risk Phrases:

R-Phrase	Description	
R-		
EU Safety Ph	ISes:	
S-Phrase	Description	
S-		

Details of international registration status

Listed on or in accordance with the following inventories: EINECS - Europe ECL - Korea ENCS - Japan

AICS - Australia IECSC - China DSL - Canada PICCS - Philippines TSCA - USA

16. Other information

16.1 Additional information:

This Material Safety Data Sheet (MSDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe

Material Safety Data Sheet

Material: 60005014

ELASTOSIL® LR 3003/40 A

Date of last alteration: 19/12/2012

Version: 1.1 (US)

Date of print: 05/28/2014

valid patents or as extending a license under valid patents. This MSDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

ASTM D3278, DIN 55680, ISO 3679 Setaflash or Rapid closed cup DIN 51755 Abel-Pensky closed cup

All deliveries are subject to the WACKER SILICONES Health Care Policy, which is available at www.wacker.com.

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial	ppm - Parts per Million
Hygienists	SARA - Superfund Amendments and Reauthorization Act
DOT - Department of Transportation	STEL - Short Term Exposure Limit
hPa - Hectopascals	TSCA - Toxic Substances Control Act
mPa*s - Milli Pascal-Seconds	TWA - Time Weighted Average
OSHA - Occupational Safety and Health Administration	WHMIS - Canadian Workplace Hazardous Materials
PEL - Permissible Exposure Limit	Identification System
Flash point determination methods ASTM D56 ASTM D92, DIN 51376, ISO 2592 ASTM D93, DIN 51758, ISO 2719	. Tagliabue (Tag) closed cup . Cleveland open cup

16.3 Conversion table:

Pressure:	1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa
Viscosity:	1 mPa*s = 1 centipoise (cP)